

SPRSO

BLACK (2026)

TECHNICAL MANUAL



• SPRSO-001

All rights reserved.

No part of this document may be copied and/or published by means of printing, photocopying, microfilming or by any other means whatsoever without the prior written consent of the manufacturer. This also applies to the included drawings and/or diagrams.

The information in this document is based on data that was available at the time the design, the material characteristics and the operating methods were published, meaning that this document is subject to change.

The original instructions for this manual have been written in English. Other language versions of this manual are a translation of the original instructions.

For this reason, the instructions are merely a guideline for the installation, maintenance and repair of the machine displayed on the front cover.

This document applies to the standard version of this machine.

The manufacturer therefore declines all liability for any damage arising from specifications that deviate from the standard version of the machine delivered to you.

This document has been compiled with the utmost care. However, the manufacturer cannot be held liable for any errors it contains or the consequences thereof.

Table of contents

1. Special functions	1
1.1 Water system calibration	3
1.2 Grinder calibration	6
2. Spare parts replacement	10
2.1 Brand name buckle and control panel	10
2.2 Outlet	11
2.3 Open right side panel	12
2.4 Remove back panel	13
2.5 Remove fan	13
2.6 Remove grinder	14
2.7 Remove the water counter/safety switches	15
2.8 Remove I/O board	16
2.9 Remove power board	16
2.10 Remove flash heater	17
2.11 Remove pump	18
2.12 Remove valve set	19
2.13 Remove brewer motor	21
2.14 Hose positions	22
3. Standard beverage settings (STD)	23
4. Software update instructions	24
5. Troubleshooting	26
5.1 Warning messages	26
5.2 Error messages	28
5.3 Other problems	30

General

- ▶ *Always read the safety instructions (700.403.347).
To avoid possible damage, these safety instructions must be read,
understood and followed.*
- ▶ *Manuals are subject to change, scan the QR code to retrieve current
information.*



1.Special functions

By using a 'secret key combination' special features can be activated.

1a



Standby mode:

- press and hold the button  for 5 seconds
- necessary flushes will be done
- the "goodbye" screen is turned off and only the start button is flashing slowly

► *The standby mode is a function which can be enabled for energy saving.*

► *Press the start button to end the standby mode.*

1b



Demo mode on/off:

- press and hold the button combination  and  for 10 seconds

► *The demo mode is a function which can be enabled for marketing purposes.*

► *Switch off the Sprso to end the demo mode.*

1c



Child lock on/off:

- press and hold the button combination  and  for 5 seconds

► *This function is to lock (and unlock) all controls to prevent accidental dosing.*

Reset the cleaning brewer counter:

- press and hold the button  for 10 seconds in this screen until the maintenance menu appears
 - *The counter that triggers the clean brewer message is reset.*



1d

Reset the descaling counter:

- press and hold the button  for 10 seconds in this screen until the maintenance menu appears
 - *The counter that triggers the descale message is reset.*



1e

1.1 Water system calibration

In this menu the water system can be calibrated.

With calibration the volume of the water is determined for a defined flow and time.

When finished the measured volume must be filled in.

- *The water system calibration is used to adjust the differences between the actual water delivery of the Sprso and the indicated amount.*

Necessities:

- measuring cup (with fine scale)



1.1a

Water system calibration:

- go to the "program menu" and press **start**
- select the "machine menu" and press **start**
- press < (4 times) to access "Water system calibration"



1.1b

Calibration water system:

- press **start** to confirm



1.1c

Step 1: preparation

- make sure that you have all necessities
- press > to go to the next step

1.1d



- Step 2: preparation
- follow the instructions on the screen
 - press **start** to begin the calibration

1.1e



- Step 3: dosing hot water
- wait for the next screen

1.1f



- Step 4: measure
- read the dosed water
 - press > to go to the next step

1.1g



- Step 5: measure
- press < or > to enter the measured volume
 - press **start** to confirm



1.1h

New water volume is saved:

- wait for the next screen
- exit the menu by pressing 

1.2 Grinder calibration

The grinder calibration will affect every coffee related beverage.

Necessities:

- coffee beans
- digital kitchen scales



1.2a

Grinder calibration:

- go to the "program menu" and press **start**
- select the "machine menu" and press **start**
- press < (3 times) to access "Grinder calibration"



1.2b

Calibration grinder:

- press **start** to confirm



1.2c

Step 1: preparation

- make sure that you have all necessities
- press > to go to the next step